





**Revision Date:** 05/19/2005 Issue date: 05/19/2005

#### CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: HYSOL 9430 1 QT KT Item No.: 83114 HARDENER **Epoxy Hardener** Region: **United States** Product type: **Contact Information:** 

Company address: Henkel Corporation 1001 Trout Brook Crossing

Rocky Hill, Connecticut 06067

Emergency telephone: 860.571.5100

Telephone: 860.571.5100 Internet: www.loctite.com

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous components** % **ACGIH TLV OSHA PEL OTHER** 60-100 Polyglycol diamine None None None

Proprietary

Aminoethylaminopropyl 1-5 None None None

trimethoxysilane 1760-24-3

#### 3. HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW**

Physical state: Liquid **HEALTH:** 3 FLAMMABILITY: Color: Clear 1 PHYSICAL HAZARD: Odor: Strong, Ammoniacal Λ Personal Protection: See Section 8

DANGER: CAUSES EYE AND SKIN BURNS.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE ALLERGIC RESPIRATORY REACTION. CAUSES RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Eyes, Skin, Inhalation, Ingestion

**Potential Health Effects** 

Inhalation: May cause irritation to nose and throat. May cause sensitization by inhalation.

Skin contact: This material is corrosive to eyes and skin. Brief contact may cause chemical burns. May cause

allergic skin reaction.

Severe eye irritation. Burns of the eye may cause blindness. Eye contact:

May be harmful if swallowed. Ingestion:

Existing conditions aggravated by

exposure:

Respiratory disorders. Skin disorders. Eye disorders. Asthma.

See Section 11 for additional toxicological information.

#### 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing

and shoes. Wash clothing before reuse. If skin irritation persists, call a physician.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Ingestion:** Keep individual calm. Do not induce vomiting. Drink 1 or 2 glasses of water. Get medical attention

immediately.

Notes to physician: None.

## 5. FIRE-FIGHTING MEASURES

Flash point: Greater than 149°C (300°F) Tagliabue open cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

**Extinguishing media:** Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Acrid smoke and fumes.

## **6. ACCIDENTAL RELEASE MEASURES**

Environmental precautions: No information available

Clean-up methods: Remove all sources of ignition. Keep unnecessary personnel away. Immediately contact emergency

personnel.

### 7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Avoid breathing

vapor and mist. Wash thoroughly after handling.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly

closed until ready for use.

Incompatible products: Not available

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Use a NIOSH

approved respirator if ventilation is inadequate.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to

prevent skin contact.

**Eye/face protection:** Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Clear

Odor: Strong, Ammoniacal Vapor pressure: Not available pH: Not applicable

Boiling point/range: Greater than 149°C (300°F)

Melting point/range:Not availableSpecific gravity:1.02Vapor density:8.45

Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Not available
Not available

#### 10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: None

**Incompatability:** Oxidizing agents. Water. Metals. Acids. Acrylates.

Conditions to avoid: Avoid temperatures above 294 °C (561 °F). Avoid mixing resin (Part A) and curing agent (Part B) in

batches greater than 2 pound (.9 kg) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the

potential for release of toxic gasses.

## 11. TOXICOLOGICAL INFORMATION

Product toxicity data: Not available

#### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol diamine Proprietary	No	No	No
Aminoethylaminopropyl trimethoxysilane 1760-24-3	No	No	No

#### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Polyglycol diamine Proprietary	Corrosive
Aminoethylaminopropyl trimethoxysilane 1760-24-3	Irritant, Allergen

## 12. ECOLOGICAL INFORMATION

Ecological information: Not known

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose according to EPA and local governmental regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (polyglycol diamine)

Hazard class or division:

Identification number: UN 2735

Packing group:

Exceptions: (Not more than 1 Liter) Consumer Commodity ORM-D

International Air Transportation (ICAO/IATA):

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. ( Polyglycol diamine )

Hazard class or division: 8
Identification number: UN2735
Packing group: II

WaterTransportation (IMO/IMDG):

Proper shipping name: Amines, liquid, corrosive, n.o.s. ( Polyglycol diamine )

Hazard class or division:

Identification number:

Packing group:

Marine pollutant:

8

UN2735

II

None

## 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None

CERCLA/SARA Section 302 EHS: None above reporting de minimus.

CERCLA/SARA Section 311/312:

Immediate Health Hazard
None above reporting de minimus.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

CERCLA/SARA 313:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class: D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Revised to new format.

Prepared by:

Gary Pierson, Sr. Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.